

Serie **DES+ / DIS+**

Shielded tap-offs and splitters with saddle & clamp, suitable for QPSK, QAM, and analogue signal distribution in community installations.

APPLICATION

Analogue and Digital Terrestrial TV Installations, both individual or community.

CHARACTERISTICS

- Maximum efficiency with minimum output level at headend.
- Same level between users in the same floor.
- Linear attenuation in the whole band.
- High signal levels can be used thanks to a special shielding design.
- Easy to set up.
- Weatherproof protector.
- Valid for reduced space installations.
- Valid for DiseqC signals



| MODELO | DIS 204+ | DIS 409+ | DES 211+ | DES 216+ | DES 220+ | DES 225+ | DES 411+ | DES 416+ | DES 420+ | DES 425+ | |
|---------------------------------|-----------------|---------------|----------|----------|----------|----------|----------|----------|----------|----------|------|
| Referencia | 85354 | 85355 | 85370 | 85371 | 85372 | 85373 | 85380 | 85381 | 85382 | 85383 | |
| Nº de salidas | 2 | 4 | 2 | | 4 | | | | | | |
| Banda cubierta | 5 ÷ 2300 MHz | | | | | | | | | | |
| Atenuación de paso IN-OUT | 5 - 47 MHz | 3,5 | 7,5 | 2,5 | 1,2 | 0,7 | 0,5 | 4 | 1,8 | 0,9 | 0,6 |
| | 47 - 550 MHz | 3,5 | 7,5 | 2,2 | 1,1 | 0,8 | 0,5 | 3,5 | 1,8 | 0,9 | 0,6 |
| | 550 - 862 MHz | 4 | 7,5 | 2,4 | 1,1 | 0,8 | 0,6 | 4 | 1,9 | 0,9 | 0,7 |
| | 950 - 1550 MHz | 4,5 | 8,5 | 2,9 | 1,5 | 1 | 1 | 4,2 | 2,8 | 1,4 | 1,1 |
| | 1550 - 2150 MHz | 5,5 | 9,5 | 3,2 | 1,5 | 1,2 | 1,4 | 4,4 | 3,2 | 1,9 | 1,6 |
| Atenuación de derivación IN-TAP | 5 - 47 MHz | | | 11 | 16 | 21 | 25 | 11 | 15,5 | 20 | 25 |
| | 47 - 550 MHz | | | 11 | 16 | 21 | 25 | 11 | 16 | 20 | 25 |
| | 950 - 1550 MHz | | | 11 | 16 | 21 | 25 | 11 | 16 | 20 | 25 |
| | 950 - 1550 MHz | | | 11 | 16 | 21,5 | 25 | 12 | 16 | 20 | 25 |
| | 1550 - 2150 MHz | | | 11,5 | 16,5 | 21,5 | 25 | 13 | 16 | 20 | 25,5 |
| Atenuación directa OUT-TAP | 47 - 950 MHz | | | 23 | 24 | 25 | 25 | 23 | 25 | 25 | 25 |
| | 950 - 2150 MHz | | | 20 | 21 | 25 | 25 | 23 | 25 | 25 | 25 |
| Aislamiento entre salidas | 47 - 862 MHz | 24 | 24 | 21 | 22 | 22 | 25 | 21 | 21 | 22 | 21 |
| | 950 - 2150 MHz | 22 | 22 | 21 | 22 | 22 | 25 | 21 | 21 | 22 | 23 |
| Perdidas de retorno IN | 47 - 862 MHz | 14 | 14 | 17 | 20 | 20 | 22 | 15 | 16 | 20 | 22 |
| | 950 - 2150 MHz | 12 | 14 | 20 | 20 | 25 | 17 | 18 | 18 | 18 | 19 |
| Perdidas de retorno OUT | 47 - 862 MHz | 13 | 12 | 20 | 20 | 25 | 22 | 20 | 22 | 23 | 25 |
| | 950 - 2150 MHz | 12 | 12 | 17 | 16 | 17 | 15 | 16 | 18 | 17 | 16 |
| Perdidas de retorno TAP | 47 - 862 MHz | | | 12 | 13 | 17 | 16 | 18 | 19 | 21 | 20 |
| | 950 - 2150 MHz | | | 12 | 12 | 12 | 12 | 16 | 16 | 16 | 16 |
| Paso de corriente | IN - OUT | NO | NO | SI | | | | | | | |
| 24 Vdc, 0, 5A, 22 KHz | OUT - IN | SI | SI | SI | | | | | | | |
| Paso de corriente | IN - TAP | NO | | | | | | | | | |
| | TAP - IN | NO | | | | | | | | | |
| | TAP-TAP | NO | | | | | | | | | |
| Dimensiones de embalaje | mm | 185 x 90 x 50 | | | | | | | | | |
| Unidades por embalaje | | 10 | | | | | | | | | |
| Peso | Kg | 0,85 | | | | | | | | | |

CONEXIONES

